



From Tyco Security Products

# KIT32-412HC Fire Monitoring System



## Features That Make a Difference:

### 3G2060R

- Certified for active or passive ULC fire monitoring.
- Compatible with DSC PC1616/1832/1864 control panels
- Uses HSPA (3G) network for high-speed, reliable and low-cost communications to an IP receiver
- Automatically switches to 2G (EDGE/GPRS) if 3G service is not available
- Back up and primary HSPA alarm communication
- SIM card included
- Activation and initialization via automated telephone activation system (VRU) or web-user interface provided by C24 Communications
- Compatible with Sur-Gard System I-IP/II/III/IV monitoring station receivers

## When it comes to life safety issues, every second counts.

Fast and detailed transmission in cases of fire events reduces the time between detection and onsite response from your local fire station. By choosing DSC's new fire transmission system KIT32-412HC for the installation and the monitoring of your Fire Alarm Signals, you have the assurance of a prompt intervention at your premises, 24 hours a day, 7 days a week. This Cellular Communicator kit will meet the requirements of ULC-S561 Standard for Fire Monitoring applications. It can help to provide sufficient warning so that occupants can evacuate safely as well as protect buildings and their contents.

## ULC-S561 Standards stipulates that:

- All equipment must meet the Canadian national standards and each province building code
- Installation and operation of sprinklers and fire systems must meet the requirement of ULC-S561
- Alarm installing company must be ULC listed and under the audit program
- Care contract must be in place for monitoring service

panels, keypads & modules

Contact your DSC distributor.  
www.dsc.com | 1-888-888-7838

## What is in the kit:

- PC1832 V4.6
- PC4050CR RED CABINET for commercial fire ULC installations
- T-1 TAMPER
- 2 X 7AH BATTERY
- TRANSFORMER 120V 60HZ
- PK5501 NA KYPD WITH F1-F5 FUNCTION KEYS
- TELEPHONE JACK AND CORD
- 3G2060R WITH SIM
- L-1 CAM LOCK WITH 2 KEYS

## Literature included in the kit:

- ULC INSTALL GUIDE
- POWER V4.6 INSTALL MANUAL
- POWER V4.6 USER MANUAL
- PK/RFK55XX INSTALL SHEET
- POWERSERIES WIRING DIAGRAM
- POWERSERIES QUICK REFERENCE GUIDE

## Kit Features:

- ULC listed for fire monitoring\*
- ULC label is on the left side of the cabinet
- AC status LED on keypad
- Dimensions of the cabinet:  
12"W x 14.5"L x 4.75"D  
(30.48cm x 36.83cm x 12.06cm)

\* must be used in conjunction with ULC listed communication modules: 3G2060R or TL2603GR